



# DuraRoof

# TECHNICAL DATA SHEET



## Protect and Preserve your Roof

### Product Description

DuraRoof is a patented waterborne Roof Coating designed to protect asphalt shingles and concrete tile roof surfaces. It has been wind tunnel tested to Category Five hurricane force winds and proven to prevent shingle damages. DuraRoof eliminates Granular Loss and Algae Growth and will increase the life cycle of an asphalt shingle roof 5 to 7 years with just one application.

### Applying DuraRoof

Stir well prior to use. Apply with a pump sprayer, 1/2" nap roller, or airless paint sprayer (tip size 5-17 or larger). Apply DuraRoof uniformly until thoroughly saturated and adsorbed into the surface without runs. Back roll any runs immediately before drying. For increased durability, a second coat can be applied after the first coat has thoroughly dried.

### Important Product Information

Read entire label and understand instructions before using. Application temperature must be a minimum of 50 °F and rising and surface must be completely dry with no rain prior to install. Use NIOSH approved eye and respiratory protection when applying DuraRoof.

Formulation Constants	
Non-Volatile Solids	+/- 25%
Density	+/- 8.55 (1.024 kg/l)
VOC grams/liter	142 g/l
Ph	+/- 8

### Typical Coverage Rates\*

Asphalt Shingles +/- 100 sf/ gallon  
Concrete tile +/- 125 sf/gallon  
*\*Surface texture and porosity will determine actual coverage rates.*

### Packaging

- 5-Gallons
- 55-Gallons
- 275-Gallons



### Manufactured in USA by

Enviroseal LLC  
500 Farmers Market Rd., # 18  
Fort Pierce, FL, 34982-USA  
+1-772-323-5400  
[info@enviroseal.com](mailto:info@enviroseal.com)  
[www.enviroseal.com](http://www.enviroseal.com)

Questions? Contact us for technical assistance  
[info@enviroseal.com](mailto:info@enviroseal.com)      [www.enviroseal.com](http://www.enviroseal.com)