



Duraseal Plus

TECHNICAL DATA SHEET



Breathable Stone and Masonry Sealer

Duraseal Plus is a deep penetrating formula that is easy to use, is VOC compliant, breathable, nonflammable, non-yellowing, and does not alter the appearance or texture of the treated surface. It is designed for application to above grade vertical and horizontal surfaces such as Limestone, Travertine, concrete, bricks, light weight concrete, mortar, porous brick, precast, pre-stressed, poured-in-place, and concrete wearing surfaces. It is suitable for use on interior and exterior walls, sound barriers, sidewalks, ramps, parking decks, and industrial floors.

Application of Duraseal Plus

Duraseal Plus can be applied to clean unsealed porous surfaces and is supplied ready-to-use. Duraseal Plus is best applied by low-pressure airless spray but can be applied by garden-type sprayer; small areas can be applied by brush or roller. Water repellency properties will fully develop in 24 hours to 5 days after application depending on ambient conditions. Consult SDS for safety and application guidelines prior to use.

Inspection Method	Value
Appearance	Milky White
Active content	+/- 10% by weight
Density	+/- 0,99 g/cm ³
Viscosity, dynamic at 25 °C	Approx. 12 mPa.s
pH-Value	+/- 8
VOC (ASTM 5095)	5.63 Grams/Liter

DURASEAL PLUS SPECIFICATIONS

- Ready-to-use
- Non Slippery
- Water based formula
- VOC < 6 grams/liter
- Colorless, odorless,
- Non-glossy
- Resists alkalinity
- Resists chloride salts
- Won't change texture

Approximate Coverage Rates*

Brick:	150 to 250 ft ² /p/gallon
Concrete:	100 to 450 ft ² p/gallon
Stucco:	100 to 300 ft ² p/gallon
Stone:	85 to 500 ft ² p/gallon
Paver Bricks	80 to 200 ft p/ gallon

**Depending on porosity and texture, always test first for suitability and satisfaction.*

PACKAGING

5-Gallons
55-Gallons
275-Gallons
Private labeling available

Duraseal Plus treats

- Natural Stone
- Concrete
- Brick
- Parking decks
- Sports arenas

Manufactured in USA by

Enviroseal LLC
500 Farmers Market Rd., # 18
Fort Pierce, FL, 34982-USA
info@enviroseal.com
Phone: +1-772-323-5400
www.enviroseal.com