



500 Farmers Market Rd., # 18
 Fort Pierce, FL, 34982-USA
 +1-772-323-5400 - 800-775-9474



Email: info@enviroseal.com Web: <http://www.enviroseal.com>

DuraSeal Zero™ is a clear acrylic waterborne film forming Zero VOC sealer used as both a cure and seal compound or applied to aged concrete. It is designed to protect and beautify masonry and other porous surfaces and is ideal for both interior and exterior surfaces.

USES

Seals, protects and improves concrete, brick, stucco, wood, and other porous surfaces and also used to prime surfaces prior to painting. If used as an initial cure for concrete, Duraseal Zero™ should be applied after the bleed water has disappeared while the concrete is still damp.

FEATURES

- Zero VOC
- Easy to Apply
- Water Repellent
- Non-Flammable
- No Harmful Vapors
- Chemical Resistant
- Provides glossy finish
- Cleans up with Water
- Blocks Efflorescence
- Repels Oil and Grease Stains

APPLICATION RATES AND METHODS

On aged surfaces, apply one coat of DuraSeal Zero™, a second coat can be applied if surface is very porous. DuraSeal Zero™ can be applied with a brush, roller, or airless spray equipment. Clean tools and equipment with water immediately after use and before sealer dries. Apply at temperatures between 40° and 110° F. Important Note: Always test a small area of surface to verify penetration and overall satisfaction. Typical coverage rates are 100 to 400 square feet per gallon (2.4 – 9.8 M²/Liter). Consult SDS for safety information.

CURE AND SEAL APPLICATION GUIDELINES

Apply with low pressure spray equipment with a fan-tip nozzle. For best results, Duraseal Zero™ should be applied in 2 thin layers at right angles to one another in a crosshatch pattern. Broom or roll any puddling material, a light second coat can be applied if the surface adsorbs liquid after the initial treatment dries. Apply evenly to obtain 200 to 400 feet per gallon (4.9 to 9.8 M²/Liter)

*Depending on porosity and texture, always test first for coverage rates and satisfaction

PACKAGING

- 5-gallon pails
- 55-gallon drums
- 275-gallon totes

SPECIFICATIONS

BASE	Aqueous Acrylic Copolymer
DENSITY	+/- 8.5 pounds/Gal (1.01 Kg/l)
SOLIDS	+/- 17%
APPEARANCE	Milky White – Dries Clear

Enviroseal warrants that for a period of 12 months from the date of purchase, Duraseal ZERO™ will be free of manufacturing defects and is warranted to be of uniform quality within tolerances and conforms to published specifications in force on the date. Enviroseal shall only be held liable under this warranty if the material has been stored and used in accordance with published product technical information. Enviroseal has no control over the use of this product and customer agrees to assume full responsibility for each application and Enviroseal assumes no liability for final results. Refer to SDS and other printed information for additional product details. For professional use only.

**Environmentally Safe Products
 For Today's Construction Projects**