



Duraseal Zero™

TECHNICAL DATA SHEET



- **Zero VOC** as per EPA method 24
- Produces a clear gloss finish.
- Use interior and exterior
- Solvent-free, low-odor formulation
- Rolls on milky white, dries clear
- Simple soap-and-water cleanup

Formulation Constants	
Non-Volatile Solids	+/- 12.5%
Density	+/- 8.4 (1.012 kg/l)
VOC grams/liter	2 g/l
Ph	+/- 8

Zero VOC Concrete Sealer

Duraseal Zero™ is a non-toxic water-based film forming acrylic sealer designed to provide a durable clear topcoat for porous concrete, masonry, and wood surfaces. It protects against stains and can be used indoors or outdoors and is recommended for commercial and residential projects.

Application: Surface must be clean, dry, and free of all contaminants. Duraseal Zero™ can be applied with a sprayer, nylon bristle brush, or short nap roller. Spray, brush, or roll area to be treated and back-roll to re-distribute any puddles or runs before Duraseal Zero™ dries. Enviroseal recommends only one coat of Duraseal Zero™. Protect freshly coated surfaces from rain and use of slip resistant additive is recommended for areas subjected to pedestrian traffic. Consult SDS and additional product information before use. Wear NIOSH approved eye and respiratory protection. For professional use only.

Contact us for technical assistance info@enviroseal.com or visit www.enviroseal.com

Approximate Coverage Rates*	
Brick:	125 to 175 ft ² /p/gallon
Concrete:	100 to 350 ft ² p/gallon
Stucco:	100 to 250 ft ² p/gallon
Stone:	85 to 500 ft ² p/gallon
Paver Bricks	80 to 200 ft ² p/ gallon

*Depending on porosity and texture, always test first for suitability and satisfaction.

PACKAGING
 5-Gallons
 55-Gallons
 275-Gallons
 Private labeling available

Manufactured in USA by
 Enviroseal LLC
 3601 Clover Lane, Unit G
 New Castle, PA, 16105
info@enviroseal.com
www.enviroseal.com
 Phone: 724-320-1100