

LAS-320™

TECHNICAL DATA SHEET

LAS-320™ is a polymeric asphalt sealer developed to protect asphalt surfaces from fuel spills and UV oxidation. It makes a molecular bond with asphalt surfaces that penetrates deep into cracks to provide long term protection with just one application. It also seals small cracks that helps prevent freeze-thaw damage in cold climates.

Easy to Apply! Simply spray or pour LAS-320™ on the surface and spread liberally with a push broom or spray using conventional equipment.



LAS-320™ Protects

Asphalt surfaces from Fuel, UV, and Chemical Damage.

LAS-320™ Preserves

Asphalt for up to TEN years with just one application.

LAS-320™

Has no odor, will not track, and provides Long Term protection with just one application

Packaging

5-Gallon Pails
55-Gallon Drums
275-Gallon Totes



NON-TOXIC ASPHALT SEALER

LAS-320™ is:

- ✓ Classified as a Fuel Resistant Sealer by the FAA
- ✓ Low VOC Rating 94 Grams per Liter
- ✓ Environmentally safe – No PAH
- ✓ No odor and No tracking
- ✓ Repels most liquids and chemicals.
- ✓ Eliminates UV damage.
- ✓ Non-toxic - Non-hazardous - Non-flammable
- ✓ Dries quickly- usually less than 10 minutes.
- ✓ Can be applied with a broom or sprayed.
- ✓ Coverage rate +/- 100 square feet per gallon

LAS-320™ makes a molecular bond with asphalt that adsorbs and penetrates for long lasting protection

**ONE APPLICATION CAN LAST
TEN YEARS OR MORE**



Enviroseal LLC
500 Farmers Market Rd., # 18
Fort Pierce, FL, 34982-USA
Phone : +1-772-323-5400
info@enviroseal.com
www.enviroseal.com